Knox[®] Padlocks



Fire/Law Enforcement Rapid Entry System

Exterior Padlock Features and Benefits

Knox Padlocks are operated with the same Knox Master Key used for other Knox Rapid Entry System devices. The exterior, heavy duty Knox Padlock (Model 3770) with a stainless steel shackle is designed for securing perimeter or fire access gates, industrial equipment yards and residential storage areas. The shrouded all weather padlock (Model 3772) provides additional security against pry and cut attacks.

- Rust free, all-weather stainless steel shackle
- Heavy-duty lock design and solid brass body resists pull ٠ attacks
- Lock and body cover protects padlocks from harsh weather • conditions and outdoor sprinkler systems
- Medeco[®] cylinder has a UL 437 rating not offered by most padlock manufacturers
- Choice of ID label (Fire/red, EMS/white, Police/blue, Sheriff/ gold, Security/white)

Interior Padlock Features and Benefits

The Knox interior padlock (Model 3771) is designed to secure fire sprinkler control systems, hazardous chemical supplies, restricted utility areas and equipment lockers. The UL® listed padlock resists pull attacks.

- Hardened steel shackle; 5/16" diameter shackle fits on a wider range of interior hasps
- Heavy-duty lock design and steel body resists pull attacks ٠
- Medeco cylinder has a UL 437 rating not offered by most padlock manufacturers
- Choice of ID label (Fire/red, EMS/white, Police/blue, Sheriff/gold, • Security/white)

Typical application showing the Knox padlock daisy chained with the property owner's padlock allowing entry by either party.

Knox[®] Rapid Entry System

The Knox Company manufactures a complete line of high security products including Knox-Box key boxes, key vaults, cabinets, key switches, padlocks, locking FDC caps, plugs and electronic master key security systems. For more information or technical assistance, please call Customer Service at 1-800-552-5669.





Model 3772


Interior Use Model 3771




Ordering Specifications

To ensure procurement and delivery of the Knox® Exterior and Interior Padlocks, it is suggested that the following specification paragraph be used:

1 3 1	1	r	r
	SHROUDED EXTERIOR Model 3772	EXTERIOR Model 3770	INTERIOR Model 3771
Padlock:	Heavy-duty UL Listed cylinder.	Heavy-duty UL Listed cylinder.	Heavy-duty UL Listed cylinder.
Lock:	Double-action rotating tumblers and hardened steel pins accessed by a biased cut key.	Double-action rotat- ing tumblers and hardened steel pins accessed by a biased cut key.	Double-action rotating tumblers and hardened steel pins accessed by a biased cut key.
Finish:	Solid brass body and cylinder with EPDM rubber seal and body cover, stainless steel shackle.	Solid brass body and cylinder with brass lock cover, EPDM body cover and stainless steel shackle.	Hardened steel body and shackle with a brass cylinder.
P/N:	Knox Padlock 3772	Knox Padlock 3770	Knox Padlock 3771
Mfr's Name:	KNOX COMPANY	KNOX COMPANY	KNOX COMPANY





2-3/8

3-3/4"H x 2-3/8"W x 1-3/8"D 7/16" diameter shackle

Model 3770 4-7/8"H x 2-1/2"W x 1-7/16"D 7/16" diameter shackle

Model 3771 5"H x 2-1/16"W x 1-3/16"D 5/16" diameter shackle

KNOX COMPANY • 1601 W. Deer Valley Road, Phoenix, AZ 85027 • (800) 552-5669 • (623) 687-2300 • Fax (623) 687-2299 • Web: www.knoxbox.com • E-mail: info@knoxbox.com © Copyright 2008. Knox Company MKT-KBSPEC-0028-C



3770 Lock Cover Detail