RADIUS WALL SCONCE



The RWSC Series radius wall sconce offers maximum versatility with multiple light sources and finishes. The available combination of uplight/downlight washes the building facade while the radial soft form housing will complement similar architectural design elements.



Fixture Specifications

FEATURES

- Durable cast aluminum housing
- Available in various lighting distributions for maximum versatility
- Integrated design eliminates high angle brightness
- Luminaire finished in weatherproof powder-coat paint Dark Sky compliant

DIMENSIONS

- Completely sealed, flat tempered glass lenses suitable for use in wet location
- Ships complete with lamp
- · Downlight only, full cut-off



ORDERING INFORMATION

SAMPLE CATALOG NUMBER



A	E	6
7.25	18.0	9.0"

SERIES	
RWSC	Radius Wall Sconce
WATEVAL	E/SOURCE
70PMH	70 watt pulse start metal halide
100PINH	100 watt pulse start metal halide
150PMH	150 watt pulse start metal halide
70HPS	70 watt high pressure sodium
100HPS	100 watt high pressure sodium
150HPS	150 watt high pressure sodium
26QF	26 watt quad tube fluorescent
32TRF	32 watt triple tube fluorescent
42TRF	42 watt triple tube fluorescent
226QF	2x26 watt quad tube fluorescent
232TRF	2x32 watt triple tube fluorescent
242TRF	2x42 watt triple tube fluorescent
BOLED	30 watt LED ³

UD	Up/Downlight	
WD	Downlight only (wide distribution)- standard	
FT	Downlight only (forward throw)	
伍江	ISH	
DB	Dark Bronze	
BK	Black	
WH	White	
ps	Platinum Silver	

VOLTA	
120	120 volt
277	277 volt
WIT	Multi-Tap
OPTIO	MS
QSL.	Quartz re-strike with lamp
F	Single fusing
FF	Double fusing
EM12	1 MRII/MR16 two pin socket for 12v power
	(by others) 35w max. 35w MR11 lamp
	included.
2EM12	2 MRII/MR16 two pin sockets for 12v
	power (by others) 35w max. 35w MR11
	lamp included.
P.Tadas	SORIES
EM	Remote emergency ballast (fluorescent only)



Performance Designed Lighting Products

www.securitylighting.com

1085 Johnson Drive & Buffalo Grove, IL 60089 • TOLL-FREE: 800-544-4848 • PHONE: 847-279-0627 • FAX: 847-279-0642