

1. All plant materials shall be Florida No. 1 or better as set forth by the Florida Department of Agriculture, Grades and Standards for Nursery Plants, part I (current edition) and part Il (current edition). All tree trunk calipers shall be measured at

Landscaping shall be placed to edge of abutting streets, canals,

2. Palms shall be planted so that all heads are clear of building

varieties and all other single trunk, upright varieties with six foot (6') of clear trunk or greater shall be staked as detailed. 4. All trees shall be planted so that heads will be clear of building walls and windows at mature spread. Trees shall not be located closer that twenty feet (20') from light poles. Locations of all trees planted in Rights-Of-Way or utility easements shall be confirmed by the landscape contractor with

5. All trees and Palms shall be kept in an upright position. Under no circumstances shall any support method used employ the driving of nails or other mechanical devices of any kind into the bark of any tree or palm. Trees rejected due to this type of damage 以置言 shall be replaced with the inspector on site. Burlap material, wire cages, plastic straps, etc. must be cut and removed from the top one-h群色面云 (1/2) of the root ball. Trees grown in "grow bag" type of materials must have the "grow bags" removed entirely prior to planting the tree.

6. All major trees within or overhanging pedestrian areas shall have a clear trunk high enough to allow unobstructed pedestrian

7. All hedges shall be planted with twelve inches (12") clear space between outer branches and building walls, fences or pavement edges at the time of planting. Required hedge plants shall be planted with branches touching, as required by municipal code. All mechanical equipment, air conditioning, irrigation pumps, FPL transformers, pool pumps, etc., must be screened on three (3) sides

system with 100% coverage and a minimum of 50% overlap of spray. Irrigation rain sensor shall be installed. Irrigation water shall not be directed onto or over impervious surfaces. Irrigation systems shall operate and be designated to operate between the hours of 5:00 PM and 8:00 AM. Irrigation systems other than City water shall require a South Florida Water Management District water use permit "F prior to the issuance of the required irrigation permit from the City and/or the operation of the irrigation system. Approved irrigation

9. Planting soil shall be at least 50% muck and 50% sand pulverized and weed free, to be mixed with existing soil free from rocks and debris and backfilled into plant pits by washing in. Planting soil for Sabal Palms shall be clean sand. Existing soil may be used for planting soil if approved by the Landscape Architect. 10. Fertilizer for trees and shrubs shall be a general purpose 50% organic fertilizer (6-6-6) with minor elements, iron and

Fertilizer for palms shall be a palm special type to include Application rates for all fertilizers at the time of planting shall be 1/2 the manufacturers recommendations for established

11. Mulch shall be shreaded cypress, eucalyptus or florimulch grade "B" or better set at a 2" minimum depth and wet down to

12. Sod shall be Stenotaphrum secundatum "Floritam" solid sod, weed free and set with staggered joints. Sod shall be placed on all areas not used for buildings, vehicular use areas, walks or planting beds and shall extend to any abutting street pavement edge and to the mean waterline of any abutting canal, lake or waterway. Sod shall be placed no closer that two (2) feet from

13. Planting plans take precedence over plant lists. The Landscape Contractor shall be responsible for doing his own takeoff. The Landscape Contractor shall familiarize himself with the municipal code and deed restrictions of the City of Coconut Creek. All existing codes, specifications, and deed restrictions shall apply. All landscaping shall meet or exceed these minimum

requirements as stated in the City of Coconut Creek Land Development Code. The more stringent requirements shall apply. 14. The Landscape Contractor shall be aware of the locations of all easements and utilities above and below ground and coordinate plant locations before digging operations begin. All

15. The Landscape Contractor shall provide a written guarantee to the Owner for all plant materials and workmanship for a period no less than ninety (90) days from the time of final inspection At the end of the guarantee period, all plant materials shall be

inspected by the Landscape Contractor and the Owner. All plants that are in a healthy, growing condition at the time of the inspection shall be free from further guarantee and shall be the Owners responsibility. All plants that are in questionable condition due to transplant shock shall continue under the guarantee until recovery or, if deemed severely retarded in growth or dead, shall be replaced. Replaced plant material shall be guaranteed for the same time period and under the same conditions as the original plant material. This guarantee does not apply if the plant materials have not been maintained by the Owner as instructed by the Landscape Contractor, are damaged by storms, vandalism, insect or freeze damage or acts of God beyond the Landscape Contractors control. All plants shall be free from harmful plant pests at the time of planting. 16. Sight distance concerns must be maintained for clear sight visibility

from thirty (30) inches to seventy-two (72) inches, tree trunks excluded. 17. All site amenities to include street and internal lighting, landscaped common areas, entrances, open space, irrigation, buffers, etc. leading to and including the first certificate of occupancy, must be completed and functional prior to the issuance of the requested certificate of occupancy. 18. All common area landscape shall require permits from the City prior

RIGHT OF these by these by and of designs, the exprant To the by with all time of

FOOD FOR CONUT CREEK, I

LYONS ROAD, O